

PressureGuard® APM



Therapy Provided

- ✓ Powered Pressure Redistribution
- ✓ Alternating Pressure

QUICK FACTS

Indications

- Treatment of Stage 1-4 pressure injuries
- Patients that can't/won't reposition frequently
- Patients that can be positioned off pressure injury in at least two positions
- Prevention for high risk patient

Key Advantages:

- Simple operation
- Powered flotation mode
- Gentle and efficient pressure changes
- PressureGuard® design: stability, safety, anti-shearing

Unlike other alternating pressure mattresses, the PressureGuard APM won't create extreme pressure gradients between inflated and deflated cylinders.

On top, the Geo-Matt anti-shearing surface forms a comfortable, therapeutic interface between the air system and the user. It absorbs and smooths sharp pressure drop-offs that other surfaces can't, while the air system does the "heavy lifting" below, alternating weight-bearing across the surface in ten-minute cycles. Or, select "Float" mode for effective powered flotation.

Other standard PressureGuard features include the exclusive Heel Slope taper, and two-part Safety-Edge bolster system for added stability when sitting or transferring. Bacteriostatic top fabric is fluid-proof, fire resistant, tear resistant, cleanable, and replaceable.

Item #	Description
5175-29	PressureGuard® APM, w/standard control unit, 75"L x 35"W x 7"H
5180-29	PressureGuard® APM, w/standard control unit, 80"L x 35"W x 7"H
5184-29	PressureGuard® APM, w/standard control unit, 84"L x 35"W x 7"H
5500	Standard control unit only

Medicare Approved: E0277 (Group II)

Weight limit: 350 lbs.

Warranty: 18 months non-prorated.

Mattress weight: 20 lbs.

Control unit: 5.25 lbs.

UL listed: Yes

The PressureGuard® APM is recognized for reimbursement under Medicare Code: E0277. All models are fire barrier version (FBV) as indicated by "-29" suffix, denoting certified conformance to NFPA 101 (Life Safety Code); Cal Tech Bulletin #117; 16 CFR Parts 1632 and 1633; and BFD IX-11.

